

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION


Product ID: STAINLESS STEEL CLEANER
Product Name: STAINLESS STEEL CLEANER
Revision Date: Apr 11, 2022 **Date Printed:** Jan 30, 2025
Version: 3.0 **Supersedes Date:** Feb 16, 2022
Distributor's Name: EDMER SANITARY SUPPLY COMPANY, INC.
Address: 519 East Meadow Avenue, East Meadow, NY 11554
Emergency Phone: 1-800-535-5053
Information Phone Number: (516) 794-2000
Fax:
Product/Recommended Uses: Stainless Steel Polish

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 1
Gases Under Pressure - Liquefied Gas
Aspiration Hazard - Category 1
Eye Irritation - Category 2A
Skin Irritation - Category 2
Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves, eye protection and face protection.

P261 - Avoid breathing mist, vapors or spray.

P271 - Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	41% - 67%
0068476-86-8	Petroleum gases, liquefied, sweetened	7% - 16%
0000067-64-1	ACETONE	6% - 13%
0008042-47-5	MINERAL OIL	6% - 13%
0063148-62-9	SILICONE	3% - 6%
0000119-36-8	METHYL SALICYLATE	0.2% - 3%
0000109-87-5	DIMETHOXYMETHANE	0% - 0.4%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed, unwell, or concerned: Call a POISON CENTER or doctor.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical attention.

Ingestion

Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

Most Important Symptoms and Effects, Acute or Delayed

No data available.

Immediate Medical Attention and Special Treatment, if necessary

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Do not direct a solid stream of water or foam into hot, burning pools this may result in frothing and increase fire intensity.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them.

Store at temperatures below 120°F.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
ACETONE	1000	2400			1			250
DIMETHOXYMETHANE	1000	3100			1			1000
ISOPARAFFINIC PETROLEUM DISTILLATE	500	2000			1			
MINERAL OIL								
Petroleum gases, liquefied, sweetened	500	2000			1			

Chemical Name	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
ACETONE	590				250		500	
DIMETHOXYMETHANE	3100				1000			
ISOPARAFFINIC PETROLEUM DISTILLATE					(L)[N159](L)[N800]	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];		
MINERAL OIL					(L)	[(L)]; [5 (I)];		
Petroleum gases, liquefied, sweetened								

(L) - Exposure by all routes should be carefully controlled to levels as low as possible

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	6.48 lb/gal
Density VOC	0.97 lb/gal
VOC Actual(g/l)	116.40 g/l
% VOC	15.0%

Appearance	N.A.
Odor Description	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal storage and handling conditions.

Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid heat, sparks, flame, high temperature and contact with incompatible materials.
Dropping containers may cause bursting.

Incompatible Materials

Avoid strong oxidizers, reducers, acids, and alkalis.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely Route of Exposure

Inhalation, ingestion, skin absorption.

Skin Corrosion/Irritation

Causes skin irritation

Serious Eye Damage/Irritation

Causes serious eye irritation

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Aspiration Hazard

May be fatal if swallowed and enters airways

Acute Toxicity

Based on available data, the classification criteria are not met.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Toxic to aquatic life with long lasting effects

Persistence and Degradability

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable

0008042-47-5 MINERAL OIL

Inherently biodegradable, but not readily biodegradable.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.

Bioaccumulative Potential

No data available.

Mobility in Soil

0000067-64-1 ACETONE

The substance is not PBT / vPvB.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Floats on water. Contains volatile constituents. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0008042-47-5 MINERAL OIL.

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

UN1950, Aerosols, 2.1 (LTD QTY)

IMDG Information

UN1950, Aerosols, 2.1 (LTD QTY)

IATA Information

UN1950, Aerosols, flammable, 2.1 (LTD QTY)

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	41% - 67%	Canada NPRI, DSL, SARA312, VOC, TSCA
0068476-86-8	Petroleum gases, liquefied, sweetened	7% - 16%	DSL, SARA312, VOC, TSCA
0000067-64-1	ACETONE	6% - 13%	DSL, CERCLA, SARA312, VOC exempt, TSCA, RCRA
0008042-47-5	MINERAL OIL	6% - 13%	DSL, SARA312, TSCA
0063148-62-9	SILICONE	3% - 6%	DSL, SARA312, VOC exempt, TSCA
0000119-36-8	METHYL SALICYLATE	0.2% - 3%	DSL, SARA312, VOC, TSCA
0000109-87-5	DIMETHOXYMETHANE	0.0% - 0.4%	DSL, SARA312, VOC, TSCA
0006485-40-1	2-Cyclohexen-1-one, 2-methyl-5-(1-methylethenyl)-, (5R)-	Trace	DSL, SARA312, TSCA

Product does not contain any chemicals listed under California Proposition 65

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; N.A. - Not Available; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 2
FLAMMABILITY	4
Physical Hazard	0
Personal Protection	B

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.